

Vista T P


Vista T P 910, Vista T P 810, Vista T P 710, Vista T P 610, Vista T P 510
13 BTE hearing aid series



P 13

Soundscape Manager		910	810	710	610	T 500
Auto Sound Control	Music	•	•			
	Noise	•	•	•		
	Conversation in a crowd	•	•	•		
	Conversation in a small group	•	•	•		
	Conversation in quiet	•	•	•	•	
	Conversation in noise	•	•	•	•	
	Quiet	•	•	•	•	
	Total environments	7	7	6	3	AutoMic
Speech Target Pro	Speech Target Pro	•	Speech Target 2 Speech Target			
	Speech Finder	•	•	•		
	Speech Lock	•				
	Dynamic Sound Mapping	•				
Sound Director	Speech intensifier	•	•	•	•	•
	Noise reduction	•	•	•	•	•
	Adaptive directionality	Multiband	Multiband	Multiband	Multiband	•
Sound Mapping	Sound Mapping	Dynamic	Personalized	•		
	Pinna Effect	•	•	•	•	•
Sound Suite						
	Pulse protector 2	•	•	•	•	•
	Wind control	•	•	•	•	•
	Feedback manager	•	•	•	•	•
	Natural Sound	•	•	•	•	•
Experience innovations						
	Capture All	•	•	•	•	•
	Data logging	•	•	•	•	•
	Trial	•	•	•	•	•
	Upgrade		•	•	•	•
Convenience						
	Wireless synchronization	•	•	•	•	•
	Telecoil and auto phone	•	•	•	•	•
	Binaural Phone	•	•	•	•	
Fitting						
	Automatic Adaptation Manager	•	•	•	•	•
	Music Equalizer	Binaural	Binaural	•	•	•
	Frequency compression	•	•	•	•	•
	Tinnitus masker	•	•	•	•	•
	IntelliVent	•	•	•	•	•
	Streaming programs	•	•	•	•	•
	Manual programs	•	•	•	•	•
	NAL-NL2/NL1 and DSLv5	•	•	•	•	•
	Fitting channels	20	20	16	10	6

Fitting guides



--- Slim tube (power dome)

Vista T P is rated IP 68

ANSI 3.22 2014/IEC 60118-7 2005 2cc coupler technical data

	Reference test frequency - IEC 60118-7 (kHz)	2.5	1.6
	OSPL90		
	Maximum (dB SPL)	126	131
	HFA - OSPL90 (dB SPL)	111	125
	at RTF (dB SPL)	110	125
	Full on gain (input 50 dB SPL)		
	Maximum (dB)	58	66
	HFA - FOG (dB)	51	58
	at RTF (dB)	49	60
	Reference test setting (RTS)		
	Frequency range (Hz)	<100 - 4600	<100 - 5300
	Reference test gain (dB)	34	48
	Current drain at RTS (mA)	1.15	1.15
	Typical battery life (h)	270	270
	Equivalent input noise at RTS (dB SPL)	18	19
	Total harmonic distortion at 500 Hz/800 Hz/1600 Hz (%)	0.2/0.2/0.5	1.7/1.2/0.7
	Induction coil sensitivity (31.6 mA/m)		
	HFA SPLITS/STS-RSETS (dB SPL/dB)	94/0	108/0
	Standard: mic at 70 dB SPL vs induction coil at 100 mA/m		
Electromagnetic compatibility			
EMC immunity by ANSI c63.19-2011 EMC, omni/telecoil		M4/T4	M4/T4

IEC 60118-o OES coupler technical data

	Reference test frequency - IEC 60118-o (kHz)	2.5	1.6
	OSPL90		
	Maximum (dB SPL)	130	135
	at RTF (dB SPL)	119	132
	Full on gain (input 50 dB SPL)		
	Maximum (dB)	62	71
	at RTF (dB)	60	68
	Basic frequency response		
		Frequency range (DIN 45605) (Hz)	<100 - 5300
Reference test gain (dB)		44	57
Current drain at RTG (mA)		1.15	1.15
Typical battery life (h)		270	270
Equivalent input noise at RTG (dB SPL)		19	19
Total harmonic distortion at 500 Hz/800 Hz/1600 Hz (%)		0.5/0.5/0.9	1.3/1.0/1.0
		Induction coil sensitivity	
	at RTF (graph shown for 31.6 mA/m at RTG) (dB SPL)	104	117
Electromagnetic compatibility			
EMC immunity by IEC 60118-13, 2011 field strength		24/19/19	24/19/19
90/50/35 V/m, omni. IRIL low/medium/high band (dB SPL)			

Legend

- Earhook
- Slimtube

Test conditions

Earhook: filtered; Battery size: 13; Source: voltage 1.3 V; Tubing: length 25 mm, inside diameter 1.93 mm
 The hearing instrument is set to Vista:fit test settings. LLE is applied at an approximate level of 35 dB SPL.
 Domes should never be fit on patients with perforated eardrums, exposed middle ear cavities, or surgically altered ear canals. In the case of such a condition, we recommend use of a customized earmold.
 Sound pressure level of these hearing aids exceeds 132 dB SPL.
 We reserve the right to change specification data without notice as improvements are introduced.